




KSS-15X25-HS - 1½" X 2½" Stainless Steel Residential Hinge (Set of 2)

A robust and reliable hinge engineered for high-traffic industrial and commercial gates.



Technical Specifications

Post Size	1¾" (or larger)
Application	Steel Frame Gates 1½" or larger
Adjustment	½" - 1½"
Material	Stainless Steel
Clevis Pin	¼" 300 Stainless Steel Stainless Steel Keeper
Stainless Steel is Marine Grade (304-2B) Meets or exceeds all recommended specifications for Local, State, and Federal Requirement	
Proprietary Bushing Material never needs lubrication. Eliminates metal on metal wear for life-time trouble-free operation.	

Features & Benefits

✓ **Enhanced Durability**

Engineered from heavy-duty, 100% stainless steel to deliver superior strength, lifetime rust prevention, and impact resistance.

✓ **Superior Weather Protection**

Advanced E-Coat finish prevents rust and corrosion, ideal for outdoor installations.

✓ **Smooth & Quiet Operation**

Precision design minimizes friction, ensuring effortless gate swing.

✓ **Easy Installation**

Pre-drilled holes and standardized dimensions allow for quick and secure mounting.

✓ **Professional Aesthetic**

The sleek black finish provides a clean, professional look for any fencing project.



Product Data Sheet

Revision Date: 7/23/1999

Product Number: 8702-9000

Product Name: JASAXXG

Production Description: LOW GLOSS BLACK URETHANE

Product Characteristics:

 Specific Gravity: 1.44 +/- .05

 Storage Temperature: < 80 F

Particle Distribution: +44 MICRONS (325 MESH) 18-24%

Film Thickness: 1.5 To 3.0 MILS

Cure Schedule:

10	Minutes@	400	F
18	Minutes@	375	F
25	Minutes@	360	F

Gloss: ASTM D523 17 - 25 %

Pencil Hardness: ASTM D3363 2H

Flexiblility: ASTM D522 1/8 INCH

Adhesion: ASTM D3359 5B

Direct Impact: ASTM D2794 80 IN/LBS @ 1.5 MILS

Reverse Impact: ASTM D2794 60 IN/LBS @ 1.5 MILS

Notes:

Prepared By: JACK SLADE